



WPO 14-25 E

Polishers

Extremely powerful angle polisher for refurbishing paintwork.

Product number: 7 221 49 51 01 0

Details

- > Ideal speed range with infinitely variable speed control for professional surface processing on vehicles and boats.
- > Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- > Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN high-power motor.
- > Excellent handling.
- > Spindle lock.
- > Right or left-handed operation.
- > Restart protection.
- > Soft start.
- > H 07 industrial cable.
- > Dustproof ball bearing.
- > Carbon brushes with self cut-off function.
- > Comprehensive range of accessories available.
- > Tool also available without accessories (7 221 49).

Price includes

- ✓ 1 anti-vibration handle
- ✓ 1 Support plate with Velcro attachment, Ø 150 mm
- ✓ 1 Grip hood
- ✓ 1 Polishing sponge, Ø 150 mm, medium

Product feature

- ✓ Soft start
- ✓ FEIN high-power motor
- ✓ Restart protection
- ✓ Spindle lock



Application

Polishing	★★
Rough sanding	★★
Fine sanding	★★
Dry sanding	★★
Micro-sanding	★★

★ suitable
 ★★ well suitable

Technical data

TECHNICAL DATA

Input	1,200 W
Output	750 W
Speed, no load	900 - 2,500 rpm
Polishing disc Ø	230 mm
Mounting thread	M 14
Cable with plug	4 m
Weight according to EPTA	2.50 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	84 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	95 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	100 dB 3 dB
Vibration value 1 α_{hv} 3-way	$\alpha_{h,P}$ 3,5 m/s ²
Vibration value 2 α_{hv} 3-way	$\alpha_{h,SG}$ 2,5 m/s ²
Uncertainty of measured value K α	1,5 m/s ²

Application examples

